


width \ length	42 mm		52 mm		56 mm		62 mm		68 mm		75 mm		80 mm		100 mm		125 mm										
	Pcs.	Vol. [m³]	Pcs.	Vol. [m³]	Pcs.	Vol. [m³]	Pcs.	Vol. [m³]	Pcs.	Vol. [m³]	Pcs.	Vol. [m³]	Pcs.	Vol. [m³]	Pcs.	Vol. [m³]	Pcs.	Vol. [m³]									
3,000 mm	1000	3.4	840	3.4	800	3.5	720	3.5	640	3.4	600	3.5	560	3.5	440	3.4	320	-									
2,750 mm		3.1		3.1		3.2		3.2		3.1		3.2		3.2													
2,700 mm		3.0		3.0		3.0		3.1		2.9		3.0		3.0													
2,600 mm		2.8		2.8		2.9		3.0		2.8		2.9		2.9													
2,500 mm		2.7		2.7		2.8		2.9		2.7		2.8		2.8													
2,400 mm		2.6		2.6		2.7		2.8		2.6		2.7		2.7													
2,300 mm		2.6		2.6		2.6		2.7		2.5		2.6		2.6													
2,250 mm		2.6		2.6		2.6		2.6		2.5		2.6		2.6													
2,200 mm		2.5		2.5		2.6		2.6		2.5		2.6		2.6													
2,100 mm		2.4		2.4		2.4		2.4		2.4		2.4		2.4													
2,050 mm		2.3		2.3		2.4		2.4		2.3		2.4		2.4													
2,000 mm		2.3		2.3		2.3		2.3		2.3		2.3		2.3													
1,900 mm	1040	2.2	840	2.2	800	2.2	720	2.2	640	2.1	600	2.2	560	2.2	440	2.2	320	2.0									
1,800 mm		2.0		2.0		2.1		2.1		2.0		2.1		2.1													
1,700 mm		1.9		1.9		2.0		2.0		1.9		2.0		2.0													
1,600 mm		1.8		1.8		1.9		1.9		1.8		1.9		1.9													
1,500 mm		1.7		1.7		1.7		1.7		1.7		1.7		1.7													
1,400 mm		1.6		1.6		1.6		1.6		1.6		1.6		1.6													
1,300 mm		1.5		1.5		1.5		1.5		1.5		1.5		1.5													
1,200 mm		1.4		1.4		1.4		1.4		1.4		1.4		1.4													
1,100mm		1.2		1.2		1.3		1.3		1.2		1.3		1.3													
1,000 mm		1.1		1.1		1.2		1.2		1.1		1.2		1.2													
950 mm		1040		1.1		840		1.1		800		1.1		720		1.1		640	1.1	600	1.1	560	1.1	440	1.1	320	1.0
900 mm				1.0				1.0				1.0				1.0			1.0		1.0		1.0				
850mm	1.0		1.0	1.0	1.0		1.0	1.0	1.0																		
800 mm	0.9		0.9	0.9	0.9		0.9	0.9	0.9																		
750 mm	0.9		0.9	0.9	0.9		0.9	0.9	0.9																		
700 mm	0.8		0.8	0.8	0.8		0.8	0.8	0.8																		
650 mm	0.7		0.7	0.8	0.8		0.7	0.8	0.8																		
600 mm	0.7		0.7	0.7	0.7		0.7	0.7	0.7																		
550 mm	2080		1.2	1680	1.2		1600	1.3	1440		1.3	1280	1.2		1200	1.3	1120		1.3		880		1.3		640		1.1
500 mm			1.1		1.1			1.2			1.2		1.1			1.2			1.2								
450 mm			1.0		1.0			1.0			1.0		1.0			1.0			1.0								
400 mm			0.9		0.9			0.9			0.9		0.9			0.9			0.9								
350 mm		0.8	0.8		0.8	0.8		0.8		0.8	0.8																
300 mm		3120	1.1		2520	1.0		2400		1.0	2160		1.0	1920		1.0		1800	1.1	1680		1.0	1320	1.0		960	0.9
250 mm	0.9		0.9	0.9		0.9	0.9		0.9	0.9																	
200 mm	4160		0.9	3360		0.9	3200		0.9	2880		0.9	2560		0.9	2400	0.9		2240		0.9	1760		0.9	1280		0.8



**Solid Beech:** Lightly steamed | Calibrated thickness | Homogeneous dried to 7-9% KD | Cut-to-size after kiln drying  
**Tolerances:** Thickness: ±0.3 mm calibration tolerance | Width: ±0.5 mm | Length: ±1 mm per 1m  
**Thickness:** 23.8 mm (Invoiced thickness: 26 mm)

The standard product limits hit-and-miss to about 1mm in thickness. A special sorting with hit-and-miss limit of 0.5 mm in thickness is available at request.